

XS pH 70 Vio FOOD Portable pH Meter - Electrode 2 Pore T



TECHNICAL DATA SHEET

Performance

Temperature accuracy	±0,5 °C
Temperature compensation	0,0 ... +100,0 °C
Measuring range mV	-1000 ... +1900 mV
pH measuring range	-2,00 ... +16,00 pH
temperature measurement range	-10,0 ... +110,0 °C
pH resolution	0,01 / 0,1 pH
Temperature Resolution	0.1 °C
Working temperature	0 ... +45 °C

Features

PC Communication	Micro USB
Criteria for stability of the measure	Low - Med - High
Display	High-definition, backlit colour LCD
AQA	Yes
IP rating	57 IP
Display	Yes with icon
Inputs	BNC - RCA
Memory / Datalogger	1000 data
PH calibration points	1 ... 3 automatic values - 2 user values
Calibration Report	Yes
Recognised pH buffers	USA - NIST
Display	Si

Feeds

Power supply	3 x AA batteries 1.5 VV
--------------	-------------------------

Dimensions and weight

Dimensions (WxDxH)	188 x 85 x 45 mm
--------------------	------------------

Weight

0.4 Kg kg



Distribué par **Humeau**

Z.A. Hauts de Couëron - 11 rue des Imprimeurs

CS 24220 - 44220 Couëron - France

t. : +33 (0)2 40 93 53 53

info@humeau.com - www.humeau.com