



RO 5 /// Data Sheet

5-position digital magnetic stirrer without heating, designed for synchronous stirring. The magnetic coil technology provides noiseless and consistent stirring on all positions. Speed remains constant, even when load changes. The closed and compact design allows easy cleaning and protects the equipment against the penetration of liquids. Additionally, a removable transparent anti-slip mat is included.

m

а

- Adjustable reverse operation
- Wear free magnetic coils
- Error code display

Distribué par :

Z.A de Gesvrine - 4 rue Képler - B.P.4125 44241 La Chapelle-sur-Erdre Cedex - France t. : +33 (0)2 40 93 53 53 | f. : +33 (0)2 40 93 41 00 commercial@humeau.com





- Easy operation with touch keypad
- Suitable for continuous operation
- Speed range: 0 1200 rpm

Distribué par :

w

w

Z.A de Gesvrine - 4 rue Képler - B.P.4125 44241 La Chapelle-sur-Erdre Cedex - France t. : +33 (0)2 40 93 53 53 | f. : +33 (0)2 40 93 41 00 commercial@humeau.com

h u

m

е

а





Technical Data

Number of stirring positions	5	
Stirring position distance [mm]	90	
Speed deviation of individual stirring positions [%]	0	
Stirring quantity max. per stirring position (H2O) [I]	0.4	
Speed control	10 RPM Steps	
Speed range [rpm]	0 - 1200	
Stirring bar length [mm]	25 - 30	
Set-up plate material	stainless steel 1.4301	
Set-up plate dimensions [mm]	120 x 470	
Dimensions (W x H x D) [mm]	120 x 60 x 570	
Weight [kg]	3	
Permissible ambient temperature [°C]	5 - 40	
Permissible relative humidity [%]	80	
Protection class according to DIN EN 60529	IP 40	
Voltage [V]	100 - 240	
Frequency [Hz]	50/60	
Power input [W]	13	
DC Voltage [V=]	24	
Current consumption [mA]	500	